



CICO PRIMER (WP)

- DESCRIPTION** : **CICO Primer (WP)** is a multipurpose primer specially formulated as priming coat for concrete, plastered or wooden surface before application of decorative finish paint.
- USES** : Use as waterproof primer for concrete, plastered and P.O.P surface. It can be successfully used as a wood primer.
- FEATURES** : **CICO Primer (WP)** provides smooth and uniform finish of decorative paint. It makes surface waterproof and non-absorbent.
- TECHNICAL DATA** :
- Form - Liquid
 - Colour - White (can tinted to any colour)
 - Sp. Gravity - 1.30 ± 0.05
 - Drying time:**
 - Touch dry - 40 minutes
 - Hard dry - 5 to 6 hours
 - Re-coat Period - 6 hours
 - Flexibility & Adhesion - Excellent
- APPLICATION DATA** :
- SURFACE PREPARATION** : **For Concrete/Plastered Surface**
Any loose dust/dirt/deposit/grease/oil product on the surface shall be removed to make sure that there is no loose and any foreign material on the surface. Surface shall be washed with clean water after removing the algae and fungi growth. Any defect or surface irregularity should be rectified with either PMC mortar or **CICO Putty**.
- For Wooden Surface:**
The surface should be free from grease/oil or stains. Wooden surface be rubbed with emery paper to make it smooth and wipe with a cloth to remove the dust.
- APPLICATION** : Stir well before use. Apply a coat of **CICO Primer (WP)** directly without thinning. Allow it to dry for 4-5 hours before application of final paint. If the surface is porous and absorbent up to 10% ratio of potable water may be added to the primer. (Add 2 ltrs. of water to 20 ltrs. of primer). **CICO Primer (WP)** can be successfully applied by brush/roller.
- COVERAGE** : 12-15 Sq. mtr. per ltr.

- PACKING** : Available in 1 Ltr., 4 Ltr., 10Ltr and 20 Ltr.
- SHELF LIFE** : 6 months in unopened condition.
- STORAGE** : Store in cool & dry place. Keep container, airtight during handling/storage. Protect from extreme climatic condition.
- SAFETY** : Non inflammable and non-toxic. In case of skin contact, wash thoroughly with soap & water.
- PRODUCT INFORMATION** : Although the basic formation of our products generally unchanged, production refinements arising from continuing research and evaluation program may occasionally result in marginal changes in properties.

TECHNICAL DATA:

- **CICO** maintain a technical division with highly qualified Technical Personnel to investigate and advise on subjects related to concrete and The Construction Industry. The Division will advise on the correct use and selection of right products at the right place.
- **CICO** undertakes Consultancy Services for diagnosis and rehabilitation of distressed structures.
- **CICO** undertakes jobs as a package for total waterproofing system with Guarantee

CICO TECHNOLOGIES LIMITED

Regd.Office:A-9 Chittaranjan Park(LGF), Outer Ring Road, New Delhi-110 019

Corporate Office:'CICO House", B-360 Chittaranjan Park, New Delhi-110 019

Tel.No:91-11-26276106, 26275107, 26273411

Fax No:91-11-26274865

E-Mail:cicodel@vsnl.com/cicotech@cicogroup.com

Web Site:www.cicogroup.com